

RESPONSE

Examiner: Stephen A. HOLZEN

Serial No. 10/734,216
Atty. Docket No.: 71474.010200Listing of Claims

- 1-21. (Cancelled)
22. (Cancelled)
23. (Currently Amended) The integrated [disk type] wheel/hub motor generator and electromagnetic braking system for aircraft landing gear in accordance with claim 43, further comprising friction-type brakes connected to the base portion and configured to brake the wheel relative to the base portion in a blended braking system wherein magnetic braking is blended with conventional friction-type disk brakes.
24. (Currently Amended) The integrated [disk type] wheel/hub motor generator and electromagnetic braking system for aircraft landing gear in accordance with claim 43, wherein said pluralities of stators and rotors are configured so that interaction of their magnetic fluxes causes: converting electrical energy to rotational torque energy of the wheel, and converting rotational torque energy of the wheel to electrical energy.
25. (Currently Amended) The integrated [disk type] wheel/hub motor generator and electromagnetic braking system for aircraft landing gear in accordance with claim 43, wherein said pluralities of stators and rotors comprise conducting wire within carbon material configured so that interaction of their magnetic fluxes causes: converting electrical energy to rotational torque energy of the wheel, and converting rotational torque energy of the wheel to electrical energy.
26. (Currently Amended) The integrated [disk type] wheel/hub motor generator and electromagnetic braking system for aircraft landing gear in accordance with claim 25, wherein said conducting wire comprises a high temperature superconducting wire.

RESPONSE

Examiner: Stephen A. HOLZEN

Serial No. 10/734,216
Atty. Docket No.: 71474.010200

27. (Currently Amended) The integrated [disk type] wheel/hub motor generator and electromagnetic braking system for aircraft landing gear in accordance with claim 43, wherein said plurality of stators comprise high energy density permanent magnets within carbon material and said plurality of rotors comprise conducting wire within carbon material configured so that interaction of their magnetic fluxes causes: converting electrical energy to rotational torque energy of the wheel, and converting rotational torque energy of the wheel to electrical energy.
28. (Currently Amended) The integrated [disk type] wheel/hub motor generator and electromagnetic braking system for aircraft landing gear in accordance with claim 27, wherein said conducting wire comprises a high temperature superconducting wire.
29. (Currently Amended) The integrated [disk type] wheel/hub motor generator and electromagnetic braking system for aircraft landing gear in accordance with claim 43, wherein said pluralities of stators and rotors are configured so that interaction of their magnetic fluxes causes converting substantially all of the wheel's rotational energy into electrical energy and then into heat energy by the formation of eddy currents in at least one of said pluralities of stators and rotors.
30. (Currently Amended) The integrated [disk type] wheel/hub motor generator and electromagnetic braking system for aircraft landing gear in accordance with claim 43, wherein said plurality of rotors comprise high energy density permanent magnets within carbon material and said plurality of stators comprise steel, configured so that magnetic fluxes of the permanent magnets cause eddy currents to be generated within a stator, causing a magnetic drag torque energy to be generated within the wheel to dissipate the rotational energy of the wheel.
31. (Currently Amended) The integrated [disk type] wheel/hub motor generator and electromagnetic braking system for aircraft landing gear in accordance with claim 30, wherein

RESPONSE

Examiner: Stephen A. HOLZEN

Serial No. 10/734,216
Atty. Docket No.: 71474.010200

the plurality of rotors comprise conducting wire and the plurality of stators comprise a solid conducting material conducive to generation of eddy currents when power is applied to said wire.

32. (Currently Amended) The integrated [disk type] wheel/hub motor generator and electromagnetic braking system for aircraft landing gear in accordance with claim 30, wherein the plurality of stators comprise conducting wire and the plurality of rotors comprise a solid conducting material conducive to generation of eddy currents when power is applied to said wire.

33. (Currently Amended) The integrated [disk type] wheel/hub motor generator and electromagnetic braking system for aircraft landing gear in accordance with claim 43, wherein the aircraft landing gear comprises two wheels connected to and independently rotatable with respect to the base portion about the axis, wherein each of the two wheels is associated with a portion of the plurality of stators and a portion of the plurality of rotors.

34. (Currently Amended) The integrated [disk type] wheel/hub motor generator and electromagnetic braking system for aircraft landing gear in accordance with claim 43, wherein at least one of said plurality of stators comprises electrically conductive wires and is configured to generate a first magnetic flux substantially parallel to said axis when current passes through said wires, wherein at least one of said plurality of rotors comprises a permanent magnet configured to generate a second magnetic flux substantially parallel to said axis, and wherein the landing gear is configured to cause the wheel to rotate when said current passes through said wires by a magnetic torque interaction of the first and second magnetic fluxes.

35. (Currently Amended) The integrated [disk type] wheel/hub motor generator and electromagnetic braking system for aircraft landing gear in accordance with claim 43, wherein

RESPONSE

Examiner: Stephen A. HOLZEN

Serial No. 10/734,216
Atty. Docket No.: 71474.010200

each of said plurality of stators comprises electrically conductive wires and is configured to generate a first magnetic flux substantially parallel to said axis when current passes through said wires, wherein each of said plurality of rotors comprises a permanent magnet configured to generate a second magnetic flux substantially parallel to said axis, and wherein the landing gear is configured to cause the wheel to rotate when said current passes through said wires by a magnetic torque interaction of the first and second magnetic fluxes.

36. (Currently Amended) The integrated [disk type] wheel/hub motor generator and electromagnetic braking system for aircraft landing gear in accordance with claim 43, wherein at least one of said plurality of rotors comprises electrically conductive wires and is configured to generate a first magnetic flux substantially parallel to said axis when current passes through said wires, wherein at least one of said plurality of stators comprises a permanent magnet configured to generate a second magnetic flux substantially parallel to said rotational axis, and wherein the landing gear is configured to cause the wheel to rotate when said current passes through said wires by a magnetic torque interaction of the first and second magnetic fluxes.

37. (Currently Amended) The integrated [disk type] wheel/hub motor generator and electromagnetic braking system for aircraft landing gear in accordance with claim 43, wherein each of said plurality of rotors comprises electrically conductive wires and is configured to generate a first magnetic flux substantially parallel to said axis when current passes through said wires, wherein each of said plurality of rotors comprises a permanent magnet configured to generate a second magnetic flux substantially parallel to said axis, and wherein the landing gear is configured to cause the wheel to rotate when said current passes through said wires by a magnetic torque interaction of the first and second magnetic fluxes.

RESPONSE

Examiner: Stephen A. HOLZEN

Serial No. 10/734,216
Atty. Docket No.: 71474.010200

38. (Currently Amended) The integrated [disk type] wheel/hub motor generator and electromagnetic braking system for aircraft landing gear in accordance with claim 43, wherein said plurality of stators and said plurality of rotors are configured in a plurality of stator-rotor sets, each set comprising at least one stator and at least one rotor.

39. (Currently Amended) The integrated [disk type] wheel/hub motor generator and electromagnetic braking system for aircraft landing gear in accordance with claim 38, wherein, in each of said stator-rotor sets, at least one of said at least one stator and at least one rotor comprises electrically conductive wires configured to generate a magnetic flux substantially parallel to said axis when current passes through said wires, wherein each of said stator-rotor sets is independently operable as at least one of a motor and a generator depending on a voltage applied across said wires.

40. (Currently Amended) The integrated [disk type] wheel/hub motor generator and electromagnetic braking system for aircraft landing gear in accordance with claim 39, further comprising:

a processor connected to said stator-rotor sets; and

an electrical device comprising at least one of an electrical energy storage device and an electrical energy dissipation device,

wherein the processor is configured to connect and disconnect the stator-rotor sets to and from each other and to and from the electrical device.

41. (Currently Amended) The integrated [disk type] wheel/hub motor generator and electromagnetic braking system for aircraft landing gear in accordance with claim 40, wherein the electrical device comprises a battery.

RESPONSE

Examiner: Stephen A. HOLZEN

Serial No. 10/734,216
Atty. Docket No.: 71474.010200

42. (Currently Amended) The integrated [disk type] wheel/hub motor generator and electromagnetic braking system for aircraft landing gear in accordance with claim 40, wherein the electrical device comprises a capacitor.

43. (Currently Amended) An integrated [disk type] wheel/hub motor generator and electromagnetic braking system for aircraft landing gear, comprising:

a nose gear and a main landing gear, at least one of the nose gear or the main landing gear comprising:

a nonrotational base portion configured to connect to an airframe of the aircraft;

a wheel connected to and rotatable with respect to the base portion about a rotational axis;

a plurality of stators connected to the base portion;

a plurality of rotors connected to the wheel and configured to rotate with respect to said stators;

wherein each of said pluralities of stators and rotors is configured to generate a magnetic flux; and

wherein said pluralities of stators and rotors are configured so that interaction of their magnetic fluxes causes at least one of: converting electrical energy to rotational torque energy of the wheel, and converting rotational torque energy of the wheel to electrical energy.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER: _____**

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.